

CBR125R 2014



- 1 Powerful single-cylinder liquid-cooled engine boasts many advantages over a twin-cylinder engine of the same capacity, most noticeably lighter weight, smaller dimensions, improved fuel economy and mechanical simplicity.
- 1 Electric start means the engine is ready to go at the push of a button.
- 1 Full-size wheels, brakes and tires add to the CBR125R's sporting credentials.
- 1 Digital instrumentation includes read-outs for speed, engine revs and engine temperature as well as incorporating a fuel gauge, clock and an odometer/trip meter.



SPECIFICATIONS

Engine Type	Liquid-cooled 4-stroke single cylinder	Rear Suspension	Single shock; 126 mm (5 in.) travel
Displacement	125 cc	Tires	100/80 - 17 front; 130/70 - 17 rear
Bore & Stroke	58 mm x 47.2 mm	Brakes	Front 276 mm disc with twin-piston caliper; rear 220 mm disc with single-piston caliper.
Compression Ratio	11:1	Seat Height	795 mm (31.1 in.)
Valve Train	Chain-driven SOHC, 2 valves per cylinder	Wheelbase	1,310 mm (51.6 in.)
Fuel Delivery	PGM-FI electronic fuel injection	Curb Weight	137 kg (302 lb) including required fluids and full tank of gas - ready to ride
Transmission	Six-speed	Fuel Capacity	13 litres
Final Drive	O-ring-sealed chain	Colour	Asteroid Black Metallic, Tri-colour
Front Suspension	31 mm telescopic fork; 120 mm (4.7 in.) travel	Warranty	12 months, unlimited mileage, freely transferable warranty; extended coverage available with Honda Plus

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Motorcycle dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.
© 2012 Honda Canada Inc. All rights reserved.